

DECLARATION OF PERFORMANCE

Cinder NSBP Mixed Calibrated Project Pack

1. Product Type: Quartzitic Sandstone

2 Unique Identification Code(s): NPPCINSBPMx-PP

3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Commercial And Domestic Paving For External Use

4. Manufacturer: Natural Paving Products (UK) Ltd. (Stone Exporters (India) Pvt Ltd.)
Bhudpura
India

5. Authorised Representative: Steve Milburn

6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR: Level 4

7. Harmonised Standard: EN1341:2012

8. Notified Body: N/A

9. Declared Performance

Essential Characteristic	Performance	Harmonised Technical Specification EN1341:2012
Release Of Dangerous Substances	NPD	4.11
Compressive Strength - Lowest Expected Value	58.4MPa	EN1926 4.4
Slip Resistance Wet Value	51	EN14231 4.6.1
Slip Resistance Dry Value	61	EN14231 4.6.1
Skid Resistance	NPD	4.6.2
Freeze/Thaw Resistance – Mean values before and after freeze/thaw test	115.9/112.7MPa	EN12371 4.3.1
Freeze/Thaw Resistance – De-icing salts	NPD	4.3.2
Polishing In Use	NPD	4.6.3
Water Absorption	1.6%	EN13755
Abrasion Resistance	17.5mm	EN14157

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function: Mark Wall, Managing Director

Place and date of issue:

Belton Road
Sandtoft
Doncaster
North Lincolnshire
DN8 5SX

Signature:

A handwritten signature in black ink, appearing to read 'M. Wall', written in a cursive style.

31st March 2016