



Luxigraze 35 Tranquillity – Product Specification Sheet

PRODUCT	DESCRIPTION
Luxigraze 35 Tranquillity	Tranquillity features a super-soft, resilient pile. Manufactured using a lightweight backing and multi-tone yarn which made from the same group of plastic polymers, this range delivers both style and durability.

YARN SPECIFICATION	
Type	Polyethylene
Yarn Structure	PE monofilament straight + PE monofilament curled
Colour	4 tone

PILE SPECIFICATION	
Yarn Weight	1454 gsm ($\pm 10\%$)
Pile Height	35 mm ($\pm 5\%$)
Machine Gauge	3/8 th
Stitch Rate / 10cm	20/10cm ($\pm 10\%$)
Stitch Rate / Sq.Metre	21000 ($\pm 10\%$)

BACKING SPECIFICATION	
Primary Backing	Polypropylene + mesh scrim inlay (315 g/ m ²)
Secondary Backing	PRT (165g/ m ²)

OTHER	
Drainage hole diameter (mm)	5 (± 2 mm)
Holes Rate	1 hole every 10cm
Osmosis	>15000 mm/h
Flammability	Efl
Heavy Metal	Free (ROHS & Reach Standard)
Colour Fastness	UVB 3000H Grey Scale 4-5

MANUFACTURED ROLLS	
Width	4.00 m
Total Weight	1934 gsm ($\pm 10\%$)

GUARANTEE
This product is supplied with a 10 year UV warranty. Please refer to Luxigraze for terms and conditions.

INSTALLATION AND MAINTENANCE
This product should be installed and maintained in accordance to the products installation and maintenance guide. Details available upon request.

Luxigraze has the right to alter each product specification in order to improve the product, according to the newest technological applications. Luxigraze is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informally.