



# RESIN BOUND CLEANER



**A POWERFUL HEAVY DUTY  
CLEANER FOR RESIN BOUND  
AGGREGATE SURFACES**



## PRODUCT DESCRIPTION

Resin Bound Cleaner is an effective high-performance cleaner, which helps to remove stubborn greasy stains and heavy soiling for resin bound aggregate areas. This powerful cleaner is easy to use and has excellent degreasing properties rejuvenating your resin bound areas without damaging the surface. Formulated with biodegradable components and degreasing agents, giving you fast and long-lasting results.

## BENEFITS

- Biodegradable
- Fast acting
- Concentrated
- Easy to use
- Waterborne product
- Non-acidic

## APPLICATION

Always test a small inconspicuous area before proceeding to ensure the finished result is satisfactory.

Shake the container well before use.

Dilute by adding the following ratios of Resin Bound Cleaner to water.

**For Extremely Heavy Soiling** - Use neat and apply using a low-pressure pump sprayer or watering can, agitate with a stiff brush. Allow to act for 10-15 minutes, agitate with a stiff brush again and whilst the surface is still wet, thoroughly rinse, ensuring all residue is removed. For optimum results use warm water.

**For Heavy Soiling** - Use 1 part Resin Bound Cleaner to 3 parts water and apply using a low-pressure pump sprayer or watering can, agitate with a stiff brush. Allow to act for 5-10 minutes, agitate with a stiff brush again and whilst the surface is still wet, thoroughly rinse, ensuring all residue is removed. For optimum results use warm water.

**For General soiling** - Use 1 part Resin Bound Cleaner to 10 parts water and apply using a low-pressure pump sprayer or watering can, agitate with a stiff brush. Allow to act for 5-10 minutes, agitate with a stiff brush again and whilst the surface is still wet, thoroughly rinse, ensuring all residue is removed. For optimum results use warm water.

## STORAGE INFORMATION

Once opened use within 6 months.

Shelf life up to 5 years if stored in the original unopened container in a clean, dry area at 5°C - 25°C (41°F - 77°F)

COVERAGE	5LTR(169.1floz)
Mild cases	125m <sup>2</sup> (1340ft <sup>2</sup> )
Severe cases	75m <sup>2</sup> (800ft <sup>2</sup> )
Extremely severe cases	25m <sup>2</sup> (270ft <sup>2</sup> )

## RECOMMENDATIONS

Do not apply if rain is expected, when its frosty, or when the surface is <5°C and >25°C (<41°F and >77°F). Please be aware darker colours will have a considerably higher surface temperature in warmer weather conditions. Do not mix with any other product.

Empty containers are recyclable.

Please dispose of packaging and waste products in line with current environmental legislation.

## HEALTH, SAFETY & ENVIRONMENTAL

### KEEP OUT OF THE REACH OF CHILDREN.

**Causes skin irritation. Causes serious eye irritation.**

If medical advice is needed, have product container or label at hand. Wash hands thoroughly after handling. Wear protective gloves and eye protection. **IF ON SKIN:** Wash with plenty of water/soap. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. Dispose of contents/container in accordance with local regulations.

**Contains:** <5% non-ionic surfactants, phosphates.

**Ingredients:** [www.pavetuf.com](http://www.pavetuf.com)

**Contains: 2-BUTOXYETHANOL-TETRAPOTASSIUM PYROPHOSPHATE-(L)C9-11 PARETH-9, AMMONIA SOLUTION.**



MANUFACTURED IN THE UK



5060582651200



**WARNING**

Disclaimer: Pavetuf Resin Bound Cleaner, if used in accordance with the instructions provided, should produce results as described. Talasey Ltd does not offer nor imply any guarantees. No liability will be accepted from either the supplier nor the manufacturer, for changes in appearance or markings of the material on which it is used. Revised RBCPL0623V1.

Before use, please read the safety data sheet available on [www.pavetuf.com](http://www.pavetuf.com)

For further information or technical advice call

☎ 0330 333 8030 or ☎ (888) 240 8704



Distributed worldwide by Talasey Ltd  
[www.talasey.co.uk](http://www.talasey.co.uk)