



SEALER & RESIN RESIDUE REMOVER



**EASY TO USE SEALER & RESIN RESIDUE REMOVER FOR
USE ON OLD SPIRIT OR WATER BASED SEALERS
AND EPOXY, ACRYLIC AND SILICONE RESIDUES**



PAVETUF SEALER & RESIN RESIDUE REMOVER

PRODUCT DESCRIPTION

Sealer & Resin Residue Remover is highly effective, and easy to use. For use on natural stone or porcelain paving, this low odour, non caustic treatment is designed to soften hard to remove layers of old spirit or water based sealers and epoxy, acrylic and silicone residues left by cement free brush in jointing compounds.

This powerful remover works quickly and efficiently to remove old sealers, haze and film left by resin based, brush in jointing compounds restoring your pavings natural beauty.

BENEFITS

- High performance
- Low odour
- Non caustic
- Quick working time
- Gentle removal
- Easy to use

APPLICATION

Always test a small inconspicuous area before proceeding to ensure the finished result is satisfactory.

Shake the container well before use.

Preparation: Ensure that the surface to be treated is completely clean and dry. If necessary, first wash surfaces with Pavetuf Deep Cleaner. Rinse well with water to finish and leave to dry.

Removing Residues: Apply generously by dabbing or rolling onto the surface. Work in manageable areas at a time and do not brush out. Leave for up to 30 minutes. If drying should occur within 30 minutes apply a little more solution to keep it wet. Use a stiff short haired brush or nylon scrubbing pad to remove the softened residues from the surface. Add a little water and scrub again. Extract the released residues using a sponge or external use wet vac and rinse with water. Repeat the process if unwanted material remains.

To finish: Use Pavetuf Deep Cleaner dilute 1: 5 in warm water. Apply with a light pressure sprayer or watering can. Agitate the surface using a deck brush or nylon scrubbing pad. Rinse by hosing off thoroughly with clean water.



WARNING

TALASEY

Distributed worldwide by Talasey Ltd
www.talasey.co.uk

COVERAGE

Light Stripping

Deep Stripping

1 Litre = 10m² (33.8floz = 107ft²) 1 Litre = 5m² (33.8floz = 54ft²)

The figures indicated are approximate and should only be used as a general guideline.

STORAGE

Store in the original unopened container in a clean, dry, frost free area, ideally at 5°C - 25°C (41°F - 77°F).



RECOMMENDATIONS

Do not apply if rain is expected, when its frosty, or when the surface is <5°C and >25°C (<41°F and >77°F). Please be aware darker colours will have a considerably higher surface temperature in warmer weather conditions. Use gloves and protective goggles if there is a risk of direct contact or splashing.

HEALTH AND SAFETY

CONTAINS: benzyl alcohol.

Harmful if swallowed or if inhaled. Causes serious eye irritation.

KEEP OUT OF REACH OF CHILDREN. IF SWALLOWED: Immediately call a POISON CENTER OR a doctor. Do not breathe vapours, spray. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Please dispose of packaging and waste products in line with current environmental legislation.



Disclaimer: Pavetuf Sealer & Resin Residue Remover, if used in accordance with the instructions provided, should produce results as described. Talasey Ltd does not offer nor imply any guarantees. No liability will be accepted from either the supplier nor the manufacturer, for changes in appearance or markings of the material on which it is used.
Revised SRTG1023V3



5860582656731

Before use, please read the safety data sheet available on
www.pavetuf.com

For further information or technical advice call

☎ 0330 333 8030 ☎ (888) 240 8704