

Luxigraze 40 Luxury – Product Specification Sheet

PRODUCT	DESCRIPTION
Luxigraze 40 Luxury	Providing a top quality long lush appearance, the 40 Luxury looks & feels
	great in any garden or outdoor space. The slightly longer 40mm pile height,
	which is soft and cushioning, gives a spring meadow look all year round.

YARN SPECIFICATION	
Туре	Polyethylene and Polypropylene
Yarn Structure	C & D Shape monofilament
Dtex	7800
Colour	5 tone

PILE SPECIFICATION	
Yarn Weight	1212 gsm (±10%)
Pile Height	40 mm (±1mm)
Total Height	42 mm (±1mm)
Machine Gauge	3/8 th
Stitch Rate / 10cm	17.5/10cm (±3%)
Stitch Rate / Sq.Metre	18375 (±10%)

BACKING SPECIFICATION	
Primary Backing	Polypropylene cloth (120g/ m²)
Secondary Backing	Non-woven fabrics (60g/m ²)
Coating	Black SBR Glue (910g/ m ²)

OTHER	
Drainage hole diameter (mm)	5 ±1mm
Holes Rate	67-100 Holes/ m ²
Osmosis	1800L/H/m ²
Flammability	EN 13501 Flammability-Efl
Pull Out Force	35N/dry
Heavy Metal	SVHC ND-comply with REACH
Colour Fastness	3000H UV Grey Scale 4

MANUFACTURED ROLLS	
Width	4.00 m
Total Weight	2302 gsm (±10%)

GUARANTEE

This product is supplied with a 10 year UV warranty. Please refer to Luxigraze for terms and conditions.

INSTALLATION AND MAINTENANCE

This product should be installed and maintained in accordance with the product installation and maintenance guide. Details available upon request.

Luxigraze has the right to alter each product specification in order to improve the product, according to the newest technological applications. Luxigraze is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informally.