



## Sand Set

### Block Paving Jointing Sand



**TALASEY**  
LANDSCAPING SOLUTIONS



Sand Set is a quick and easy to use polymetric jointing sand for concrete, natural stone and clay block paving. The polymers are water activated to create a stable, flexible joint offering an alternative to basic silica joint filling sands.

Helping to resist weeds, Sand Set contains minerals with high PH values which creates a nutrient-poor environment to drastically reduce the chance that weed seeds can neither take root nor germinate in the joints.

Features & Benefits

- Firm, flexible paving joints
- Weed and frost resistant
- Water-permeable
- Pre-mixed, brush in for a quick and easy application
- Long lasting joints
- Suitable for driveways, patios and pathways
- For use on new jointing or for repointing of existing paving
- Ideal for joint widths from 3mm to 10mm and joint depths of 40mm and over
- Coverage per 20kg 6m<sup>2</sup>\*

*\*Approximate coverage based on block paving that is 200x100x60mm*

Colours



Buff



Grey

Sand Set works best on new driveways, patios and pathways where no weeds have been present. Simply brush in, vibrate the paving to ensure the sand is in the full depth of the product and activate with water allowing the polymetric technology to do the rest.

If applying to an existing block paving, prepare the area, clean to remove any old jointing material, weeds and debris. Once fully dry apply a weedkiller to prevent any remaining seeds from propagating. When treated area is dry, brush in the Sand Set, vibrate the paving and activate with water, to offer the best possible prevention from weed growth.



Preparation

Prior to installation, ensure the block paving joints, and surface are completely dry, clean and free from debris. Always wear appropriate PPE, including eyewear and a dust mask. Paving should be laid on a suitable flexible/unbound, permeable construction.

Check that joints are clear and are set to a minimum depth of 40mm and minimum width of 3mm.

Application

For best results agitate the contents in the bag to ensure that the polymer and minerals are distributed evenly, as these may have settled to the bottom of the bag.

1. Empty one bag of Sand Set at a time onto the clean, dry paving surface, and sweep to completely fill the joints.
2. Vibrate the sand into the joints with a Vibrating Plate Compactor, also known as a Wacker Plate. To avoid heavy scuffing use a rubber mat. Travel across the paving in several directions, compacting down the blocks and settling the jointing sand.
3. If required apply more Sand Set as some areas may need the joints topping up. Repeat compaction.
4. With a soft brush sweep off the excess Sand Set and use a leaf blower, on a slight angle to ensure the surface is free from sand. Where there is no access to a leaf blower sweep the area multiple times.
5. Using a hose gently mist the paving in small sections and allow the water to absorb for approximately 5 minutes. Repeat the misting process 4-5 times and with each misting application add more volume of water, as it is crucial the water penetrates the whole depth of the joint.
6. Remove any excess water from the surface of the paving with either a leaf blower or a soft brush.





#### Packaging

20kg

#### Storage

Store in a cool, dry, moisture and frost-free environment at temperatures between 5° and 30°.

#### Shelf Life

3 years from date of manufacture

*NOTE: Sand Set must be stored as recommended as any moisture that enters the bag will harden the sand.*

#### Health & Safety

Wear appropriate protective clothing, eye protection, work in well-ventilated conditions. If product enters the eyes, wash thoroughly with water and seek medical advice. In case of prolonged exposure to airborne dust concentrations, wear respiratory protective equipment that complies with the requirements of European or national legislation. Do not release large quantities into the surface water or into drains. Avoid wind dispersal.

**Before use, please read the safety data sheet available at [www.talasey.co.uk](http://www.talasey.co.uk)**

Please dispose of packaging and waste products in line with current environmental legislation.







**NATURAL PAVING**  
be inspired...



**VITRIPIAZZA**  
Vitrified Porcelain Paving



**PIRANHA**  
COMPOSITE SOLUTIONS



**Luxigraze**  
ARTIFICIAL GRASS



**Pavetuff**  
Landscape Solutions



**BAKSTEEN**  
CLAY PAVERS

## OUR SERVICE OFFER

The Talasey Team are a large network of individuals, dedicated to delivering outstanding support to our customers. From our Customer Engagement Team, Area Sales Managers and Landscaping Consultants, to our Designer & Installer Network and beyond, we are fortunate to have a loyal support network behind us. This is further supported by our empathetic corporate social principles driven through our activities with our supply chain and community. Since 2004, these assets have been central to building Talasey and they will continue to shape us for years to come.



See our website for terms & conditions.

[sales@piranhadecking.co.uk](mailto:sales@piranhadecking.co.uk)

0330 333 8030

[www.talasey.co.uk](http://www.talasey.co.uk)



PTSSIGV1