

TALASEY

LANDSCAPING SOLUTIONS

STANDARD SPECIFICATIONS
AND TECHNICAL DATA

**EGYPTIAN LIMESTONE
GALALA WHITE**



Standard Specifications and Technical Data	
Product name	Egyptian Limestone
Country of Origin	Egypt
Surface Finish	Sawn, Tumbled and Acid Washed
Surface Edges	Sawn and Tumbled
Material Type	Limestone (Sedimentary natural stone)
Sealing	Comes pre-sealed
Flexural Strength	8.61 MPa
Colour	Creamy white, pale ivory with subtle beige, off-white, and occasionally light grey or light yellowish hues with delicate veining and small, subtle fossilized shell details
Compressive Strength	121.34 MPa
Abrasion Resistance Hardness	31.6 Ha
Density	2675 kg/m ³
Water Absorption	0.17%
Modules of Rupture	13.79 MPa
Weathering	Limestone will lighten over time

Each piece of stone is unique sometimes displaying differing shades and will contain veining, blemishes, small chipping (to the corners and sides) and small holes.

Never use acid or any acid-based cleaning products on Egyptian Limestone Pavers.

Do not use any type of salt or grit on Egyptian Limestone, this could potentially lead to irreversible damage.



Galala White —————•

Version No. SSELGW0226

www.talasey.co.uk
info@talasey.co.uk
0330 333 8030